

AC HOOP PINE EXTERIOR PLYWOOD AS/NZS 2271

PRODUCT SPECIFICATIONS

Product:	A/C HOOP PINE EXTERIOR PLYWOOD
Veneer Grade:	A Grade (Face) and C Grade (Back)
Standard:	AS/NZS 2271:2004 Plywood for exterior use
Manufacturer:	Austral Plywoods – Australian Grown & Made
Product Certification:	Engineered Wood Product Association of Australasia (EWPAA) JAS-ANZ
Environmental Certification:	Responsible Wood/PEFC AS4707:2014 Chain of Custody for Forest Based Products
Veneer Timber Species:	Hoop Pine (Araucaria Cunninghamii)
Core Timber Species:	Hoop Pine (Araucaria Cunninghamii)
Sheet Size:	2400 x 1200mm, 2700 x 1200mm
Thicknesses:	3mm*, 4, 5, 6.5, 9.5, 12.5, 16, 19, 25, 32mm
Density:	600kgs/m ³ (approx.)
Glue Bond:	Permanent Type “A” Bond (Phenolic Resin)
Formaldehyde:	Emission “Super E0”
Applications:	Soffits, internal wall & ceiling linings, etc. <i>* Only available in 2400mm x 1200mm</i>

PRODUCT DESCRIPTION

Premium AC plywood has a high-grade face and a lesser grade back giving a consistent and uniform surface exhibiting a warm appearance fit for clear water-based finishing. Hoop Pine is a designated marine timber species suitable for semi exposed & interior applications where a high-quality aesthetic finish is required. Multiply is better suited where emphasis is upon a feature edge.

Take Care in Free Standing Applications

Plywood is a natural product that can be affected by changes in ambient weather conditions, possibly causing previously flat sheets to bow. For free standing applications such as kitchen/cabinet doors, Austral Door Panel is recommended.

Finishing

In semi exposed exterior applications, the product must be adequately protected by the use of a suitable water based, exterior paint or stain on both sides of the sheet & edges, irrespective of whether the sides are exposed to the weather or not. It's recommended to contact a reputable paint supplier and follow the manufacturer's instructions. Do not use oil-based products on this plywood as oil-based paints or stains may penetrate the surface veneer of the plywood and react with adhesives that bond the core veneers together. No warranty or guarantee is offered by Plywood & Panel Supplies Pty Ltd (PPS) if oil-based paint or stain has been applied to the plywood. This plywood is not suitable for use in the manufacture of doors and no warranty/ guarantee is offered by PPS if this plywood is utilised in any application associated with the manufacture of doors.

Disclaimer

The information provided herein is believed to be accurate but is not warranted to be, whether it originated with PPS or not. This information cannot be warranted by PPS to be correct or appropriate for the recipient's intended use. Recipients are advised to confirm in advance of need that the information is correct, applicable and suitable to their circumstances.