PLYWOOD + PANEL

www.plywoodandpanel.com.au

P +61 7 3279 7111 **E** info@plywoodandpanel.com.au

MDF MOISTURE RESISTANT

PRODUCT SPECIFICATIONS

Product:MDF MOISTURE RESISTANTFinish:Smooth Sanded Fine FinishManufacturer:Laminex – Trade Essentials

Standard: AS/NZS 1859.2 Environmental Certification: Green Tag Certified

Core Timber Species: Renewable Plantation Pine

Sheet Size: 2400 x 1200mm, 2400 x 1800mm, 2700 x 1200mm, 3600 x

1200mm, 3600 x 1800mm

Thicknesses: 3, 6, 9, 12, 16, 18, 25, 32mm **Density:** 700-760kgs/m³ (approx.)

Glue Bond: Melamine Urea Formaldehyde (MUF)

Formaldehyde: Emission "E0"

Applications: Kitchen cupboards, bathroom vanities, laundry cupboards,

shelving, lining

PRODUCT DESCRIPTION

Moisture Resistant Medium Density Fibreboard (MDF) a compressed wood particle fibreboard that is suitable for areas of high humidity and damp conditions such as bathroom & kitchen cabinetry where accidental wetting may occur.

Disclaimer

The information provided herein is believed to be accurate but is not warranted to be, whether it originated with PPS or not. This information cannot be warranted by PPS to be correct or appropriate for the recipient's intended use. Recipients are advised to confirm in advance of need that the information is correct, applicable and suitable to their circumstances. Always refer to manufacturers span tables for correct loadings.